

Boom Radius Feet	All Booms Retracted	Second Stage Extended	Third Stage Extended	Fourth Stage Extended	Fifth Stage Extended
5	18000	13200			
5.9	18000	13200	6500		
7.9	13200	13200	6500	5700	
9	11100	11100	6500	5700	4400
10	10000	10000	6500	5700	4400
11.5	8800	8800	6500	5700	4400
13	7700	7700	6500	5700	4400
13.5	7600	7600	6500	5700	4400
15		6800	6500	5700	4400
16.5		6100	5900	5700	4400
19.5		4850	4850	4400	4400
23		3950	3950	3700	3600
26			3400	3200	3050
29.5			2750	2750	2650
32.5			2250	2300	2200
36				1950	1950
39				1650	1750
42.5				1400	1550
46					1300
49					1100
51.2					1000

Note:

1. Rated loads on the above chart are maximum allowable load with the outriggers fully extended on firm level ground and based on the actual working radius including the deflection of the boom.
2. Weights of hook (70lbs), Slings and any accessories to the boom or load line must be deducted from the rated loads.

Available Options:

1. **Radio Remote Control**
2. **Electronic Capacity Alert (Shut Down) with Monitor**
3. **One Man Steel Basket**
4. **Two Man Steel Basket**
5. **Walk Through Operators Platform**
6. **Two Stage Steel Jib. 9.8 feet to 16.4 feet**